

Table type	Runnerblock	Load rates static			Torques static				
		Cy	Cz+	CZ-	Mx0	My0(300mm)	My0(400mm)	My0(500mm)	My0(600mm)
FKK 30-220 KGT32	MSA30S	138,6kN	220kN	165kN	12870Nm	15650Nm	24530Nm	34750Nm	46520Nm
	Balldrive	32x10	32x20	32x32		<b>Mz0(300)</b>	<b>Mz0(400)</b>	<b>Mz0(500)</b>	<b>Mz0(600)</b>
	Coa, static Balldrive	51500N	51500N	43900N		14000Nm	20900Nm	27800Nm	34800Nm
		Cy	Cz+	CZ-	Mx0	My0(350mm)	My0(400mm)	My0(500mm)	My0(600mm)
FKK 30-220 KGT40	MSA30LS	230,5kN	366kN	274,5kN	19480Nm	29220Nm	36740Nm	53130Nm	71550Nm
	Balldrive	40x10	40x40			<b>Mz0(350)</b>	<b>Mz0(400)</b>	<b>Mz0(500)</b>	<b>Mz0(600)</b>
	Coa, static Balldrive	89900N	76200N			25800Nm	31530Nm	43200Nm	54750Nm

Recommended load is 25% of loads and moment rating

